

**EVO**

## TP4 TruFlat POS Terminal

The EVO TP4 TruFlat sets a whole new standard by offering enterprise-class build quality, resistive touchscreen technologies, and the latest in high-performance Intel® processors. Available with Celeron™, Pentium™, Core i3™, Core i5™, and Core i7™ processors, the EVO TP4 thrives in the most demanding environments. The EVO TP4 has an IP54 certified rating for both dust and splash resistance.



Shown with optional MSR



Shown with optional customer display

### Key Features



#### Baytrail and Haswell Processors

Available with Intel Celeron, Pentium, Core i3, Core i5, or Core i7



#### Touchscreen

15" (381mm) zero bezel, 5-wire resistive or PCAP touchscreen technology



#### Hard Drive

2.5" (64mm) 320GB HDD or 60-120GB SSD



#### Built In Cable Management

Keeps cords out of sight



#### EZHD Slot

Makes for quick HDD or SSD replacement



#### IP54 Rating

Resistant to dust buildup and splashing water



#### Sturdy Die-Cast Aluminum Alloy Frame

Provides bump-free operation



#### Optional Accessories

Optional integrated MSR, VFD customer display, 8.4" (213mm) rear LCD display, 15" (381mm) rear LCD display, or Biometric Reader

#### ■ POS-X Warranty

##### Industry-leading Warranty Protection

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to further reduce the total cost of ownership

\*Available in USA and Canada

#### ■ POS-X Service and Support

##### 24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

MODELS	EVO-TP4C-F	EVO-TP4C-G	EVO-TP4C-H	EVO-TP4C-J	EVO-TP4C-K	EVO-TP4C-L
Processor	Intel® Celeron J1900 2.4GHz Quad Core	Intel® Celeron G1820 2.7GHz Dual Core	Intel® Pentium G3420 3.2GHz Dual Core	Intel® Core i3- 4330 3.4GHz Dual Core	Intel® Core i5- 4570S 3.6GHz Quad Core	Intel® Core i7- 4770S 3.9GHz Quad Core
Chip Set	Processor Integrated	Intel Lynx Point PCH H81				
System Memory	1 x DDR3L 2GB to 8GB	1 x DDR3 DIMM 2GB to 8GB				
Hard Drive	320GB HDD or 60-120GB SSD					
Graphic Memory	Intel Gen7 up to 854MHz	Intel® HD Graphic DX11.1				
GigaLAN (10/100/1000)	1 x RJ45					
Weight (w/base)	15 lbs (6.8kg)	15.4 lbs (7kg)				
Electrical	65W/19V	120W/19V				

PORTS	EVO-TP4C-F	EVO-TP4C-G	EVO-TP4C-H	EVO-TP4C-J	EVO-TP4C-K	EVO-TP4C-L
Parallel	1					
USB	5 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x4)	6 x USB Type A (USB 3.0 / 2.0 x2, USB 2.0 x4)				
Serial	3 x RJ45 COM3 with 5V/12V	3 x RJ45 COM3 with 5V/12V, 1 DB9				
VGA	1					
Cash Drawer Port	1					
Speakers	2					

PHYSICAL	
Housing	Die Cast Aluminum
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)
Tilt Angle	0° – 90°
Housing Color	Black
Bezel	TruFlat Zero Bezel
LCD Display	15" (381mm) LED LCD
Resistive Touch (TP4C)	5-Wire Resistive
WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year Warranty Extension
ZOE-TPC3	*3-Year Overnight Exchange
ZOE-TPC5	*5-Year Overnight Exchange

\*Available in USA and Canada



1975 Midway Lane, Suite O  
 Bellingham, WA 98226  
 sales@pos-x.com  
 360.738.8433  
 www.pos-x.com

ENVIRONMENTAL	
Ingress Protection Rating	IP54-Resistant to dust buildup and splashing water
Operating Temperature	32°F to 95°F (0°C to 35°C)
Humidity	20% to 80% non-condensing
Warranty	3-year warranty with free *2-day Advance Exchange Service
Certifications	FCC, Class A, CE, LVD, RoHs, NOM
Supported OS	POS Ready 2009 & 7/Win 7 Pro/Available with no O/S
OPTIONAL ACCESSORIES	
EVO-MR4	3 Track Magnetic Stripe Reader with USB interface
EVO-BR4	Integrated Bio Reader
EVO-RD4-VFD	Integrated 2x20 VFD Customer Display
EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD w/VGA Cable & Mount
EVO-RD4-LCD15	Integrated Rear Display, 15" (381mm) LCD w/VGA Cable and Mount
EVO-XZ4-M100	Universal VESA Mount for All Terminals and Touch Monitors